



## Features

- Recess mounted system ideal for quick installation
- Firmly fixed Santoprene gasket offers movement tractability without shearing or breaking
- Centering Bar system for wider gaps
- Extra-large sizes available
- System is suitable for full seismic movements
- Commonly used system that is easy to install and maintain
- Suitable for external applications
- Vapor Barrier is integrated with the system

### Straight Application FOS



### Corner Application FOC



FO Series

EXT. Application

Seismic Movement

WALL USE

Seal Colors:

BK

BG

WH

GY

## Details

Usage : Wall

Joint width : 1"- 24"

Optional : Fire Barrier

Application	Code	JO	SH	SW	± Movement (%)			Load (Ton)
					Horizontal	Vertical	Shear	
Straight (S)	FOS 01	42	60	42	50	50	Excellent	*
	FOS 02	51	60	51	50	50	Excellent	*
	FOS 03	76	60	76	50	50	Excellent	*
	FOS 04	102	60	102	50	50	Excellent	*
	FOS 06	152	60	152	50	50	Excellent	*
	FOS 08	203	75	203	50	50	Excellent	*
	FOS 10	254	75	254	50	50	Excellent	*
	FOS 12	305	75	305	50	50	Excellent	*
	FOS 18	457	75	457	50	50	Excellent	*
	FOS 24	610	75	610	50	50	Excellent	*
Corner (C)	FOC 01	42	60	42	50	50	Excellent	*
	FOC 02	51	60	51	50	50	Excellent	*
	FOC 03	76	60	76	50	50	Excellent	*
	FOC 04	102	60	102	50	50	Excellent	*
	FOC 06	152	60	152	50	50	Excellent	*
	FOC 08	203	75	203	50	50	Excellent	*
	FOC 10	254	75	254	50	50	Excellent	*
	FOC 12	305	75	305	50	50	Excellent	*
	FOC 18	457	75	457	50	50	Excellent	*
	FOC 24	610	75	610	50	50	Excellent	*